



SOP 25-21CW June 30, 2021

General Safety Rules – Carwash Tunnel

PURPOSE/SCOPE: The Company's primary objectives are to ensure the safety and health of our Employees, and to protect company property. Our goal is to provide safe and healthful working conditions for all Company Employees. Safety Rules have been developed to address behaviors and work practices that can lead to accidents and injuries. Each Employees must become familiar with and follow the General Safety Rules, for the carwash tunnel. Managers and Supervisors are required to enforce Safe Work practices through strict adherence to these Safety Rules.

- 1) All employees must be thoroughly trained in the safe operation and practices of working around the carwash tunnel equipment.
- 2) Unless performing a required task, do not enter the wash tunnel when the equipment is operating. *Death or dismemberment may occur.*
- 3) Do not wear loose fitting clothing or jewelry around moving equipment. Do not allow any part of your body or other objects (including ladders, hoses or tools) to come in contact with moving equipment. *Entanglement may result causing death or dismemberment.*
- 4) Do not leave ladders or any other items such as wash down hoses or tools in the wash tunnel while equipment is running. *Vehicle damage and injury, including death, can occur.*
- 5) Always exercise caution when walking (never run) through the wash tunnel, as the floor can be very slippery. Non-slip safety shoes are required to be worn, when in the tunnel.
- 6) Only those employees specifically instructed and trained, are permitted to enter the wash tunnel to perform their assigned tasks.
- 7) Emergency “STOP” buttons must be well marked and their location and proper use reviewed with all personnel. Any activated “STOP” button must be reset only by the Flight Deck Controller.

1034A Kilani Ave. # 102 Wahiawa, HI 96786 - Office: (808) 621-0899 – Fax: (808) 622-4448

www.carwash808.express



- 8) Clear the wash tunnel of any people, ladders, hoses, tools and other loose items before restarting the equipment.
- 9) An audible warning must sound, to warn people that the equipment is starting.
- 10) Do not operate any piece of equipment with safety covers removed, or improperly installed.
- 11) Do not operate any piece of equipment if any component of that piece is suspected to be defective or malfunctioning.
- 12) Store all cleaning and washing solutions in a well-ventilated area. Clean up fluid spills immediately to prevent hazardous safety conditions. Be certain to follow all safety procedures on SDS Sheets for each chemical product used.
- 13) No unauthorized people should ever be permitted in the wash tunnel or near the equipment at any time.
- 14) At least two people must be present when performing equipment repairs or preventive maintenance.
- 15) When working on any equipment that is higher than your shoulders, always use a ladder that is in good condition.
- 16) Do not perform any maintenance or work on equipment unless you first perform Lock-Out Tag-Out Safety Precautions. All electrically powered equipment must have manually operated disconnects capable of being locked in the "OFF" position. Equipment that has been "locked out" for any reason must be restarted only by the person who performed the "lock out" operation.
- 17) Do not attempt to repair or adjust any pressurized liquid or pneumatic part, hose, pipe or fitting while that equipment is in operation.
- 18) When a piece of equipment must be in operation during inspection or maintenance, one qualified person must stay at the power disconnect switch, while another qualified technician performs the inspection or maintenance.
- 19) Electrical connections and repairs must only be performed by a Licensed Electrician.

Ricky e Price
Ricky E. Price
Owner/Chairman

1034A Kilani Ave. # 102 Wahiawa, HI 96786 - Office: (808) 621-0899 – Fax: (808) 622-4448

www.carwash808.express

