SAFETY DATA SHEET



1. Identification

Product identifier BEHR® PREMIUM PLUS Exterior Semi-Gloss Enamel - Medium Base

Other means of identification

Product code 5400

Recommended use **Architectural Coating**

Recommended restrictions None known.

Manufacturer/Importer/Supplier/Distributor information

Behr Process Corp. Supplier

> 1801 E. St. Andrew Place Santa Ana. CA 92705

Telephone 714-545-7101 **Emergency telephone** +1 760 476 3962

+1 866 519 4752

Access code 335213

2. Hazard(s) identification

Physical hazards Not classified.

Health hazards Sensitization, skin Category 1A

> Carcinogenicity Category 2

OSHA defined hazards Not classified.

Label elements



Signal word Warning

Hazard statement May cause an allergic skin reaction. Suspected of causing cancer.

Precautionary statement

Prevention Obtain special instructions before use. Do not handle until all safety precautions have been read

> and understood. Avoid breathing mist/vapors. Contaminated work clothing must not be allowed out of the workplace. Wear protective gloves/protective clothing/eye protection/face protection.

If on skin: Wash with plenty of water. If exposed or concerned: Get medical advice/attention. If Response

skin irritation or rash occurs: Get medical advice/attention. Take off contaminated clothing and

wash it before reuse.

Storage Store locked up.

Disposal Dispose of contents/container in accordance with local/regional/national/international regulations.

Hazard(s) not otherwise

classified (HNOC)

None known.

Supplemental information None.

3. Composition/information on ingredients

Mixtures

Chemical name	CAS number	%
Titanium dioxide	13463-67-7	10 - 30
Diuron	330-54-1	0.1 - 1
2-Methyl-2H-isothiazol-3-one	2682-20-4	0 - 0.1

BEHR® PREMIUM PLUS Exterior Semi-Gloss Enamel - Medium Base 1/7 951421 Version #: 02 Revision date: 04-September-2020 Issue date: 16-January-2020

Composition comments

All concentrations are in percent by weight unless ingredient is a gas. Gas concentrations are in percent by volume.

The manufacturer has claimed the exact percentage as trade secret under the OSHA Hazard Communication Standard.

4. First-aid measures

Inhalation

Move to fresh air. Call a physician if symptoms develop or persist.

Skin contact

Remove contaminated clothing immediately and wash skin with soap and water. In case of eczema or other skin disorders: Seek medical attention and take along these instructions.

Eve contact

Rinse with water. Get medical attention if irritation develops and persists.

Ingestion

Rinse mouth. Get medical attention if symptoms occur.

Most important

May cause an allergic skin reaction. Dermatitis. Rash.

symptoms/effects, acute and delayed

Indication of immediate medical attention and special treatment needed

Provide general supportive measures and treat symptomatically. Keep victim under observation. Symptoms may be delayed.

General information

IF exposed or concerned: Get medical advice/attention. Ensure that medical personnel are aware of the material(s) involved, and take precautions to protect themselves. Wash contaminated clothing before reuse.

5. Fire-fighting measures

Suitable extinguishing media

Unsuitable extinguishing media

Water fog. Foam. Dry chemical powder. Carbon dioxide (CO2). Do not use water jet as an extinguisher, as this will spread the fire.

Specific hazards arising from

the chemical

During fire, gases hazardous to health may be formed.

Special protective equipment and precautions for firefighters

Self-contained breathing apparatus and full protective clothing must be worn in case of fire.

Fire fighting

equipment/instructions

Move containers from fire area if you can do so without risk.

Specific methods

Use standard firefighting procedures and consider the hazards of other involved materials.

General fire hazards No unusual fire or explosion hazards noted.

6. Accidental release measures

Personal precautions, protective equipment and emergency procedures

Keep unnecessary personnel away. Keep people away from and upwind of spill/leak. Wear appropriate protective equipment and clothing during clean-up. Avoid breathing mist/vapors. Do not touch damaged containers or spilled material unless wearing appropriate protective clothing. Ensure adequate ventilation. Local authorities should be advised if significant spillages cannot be contained. For personal protection, see section 8 of the SDS.

Methods and materials for containment and cleaning up Large Spills: Stop the flow of material, if this is without risk. Dike the spilled material, where this is possible. Absorb in vermiculite, dry sand or earth and place into containers. Following product recovery, flush area with water.

Small Spills: Wipe up with absorbent material (e.g. cloth, fleece). Clean surface thoroughly to remove residual contamination.

Never return spills to original containers for re-use. Put material in suitable, covered, labeled containers. For waste disposal, see section 13 of the SDS.

Environmental precautions

Avoid discharge into drains, water courses or onto the ground.

7. Handling and storage

Precautions for safe handling

Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Avoid breathing mist/vapors. Avoid contact with eyes, skin, and clothing. Avoid prolonged exposure. Should be handled in closed systems, if possible. Provide adequate ventilation. Wear appropriate personal protective equipment. Observe good industrial hygiene practices.

Conditions for safe storage, including any incompatibilities Store locked up. Store in tightly closed container. Store away from incompatible materials (see Section 10 of the SDS).

BEHR® PREMIUM PLUS Exterior Semi-Gloss Enamel - Medium Base 951421 Version #: 02 Revision date: 04-September-2020 Issue date: 16-January-2020

8. Exposure controls/personal protection

Occupational exposure limits

US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000)	US.	. OSHA Table Z-1	Limits for Air	Contaminants	(29 CFR 1910.1000)
---	-----	------------------	-----------------------	---------------------	--------------------

Components	Туре	Value	Form	
Titanium dioxide (CAS 13463-67-7)	PEL	15 mg/m3	Total dust.	
US. OSHA Table Z-3 (29 CFR 1910.100	0)			
Components	Туре	Value	Form	
Titanium dioxide (CAS 13463-67-7)	TWA	5 mg/m3	Respirable fraction.	
		15 mg/m3	Total dust.	
		50 mppcf	Total dust.	
		15 mppcf	Respirable fraction.	
US. ACGIH Threshold Limit Values				
Components	Туре	Value		
Diuron (CAS 330-54-1)	TWA	10 mg/m3	10 mg/m3	
Titanium dioxide (CAS 13463-67-7)	TWA	10 mg/m3		
US. NIOSH: Pocket Guide to Chemica	Hazards			
Components	Туре	Value		
Diuron (CAS 330-54-1)	TWA	10 mg/m3		

Biological limit values

Appropriate engineering

controls

No biological exposure limits noted for the ingredient(s).

Good general ventilation should be used. Ventilation rates should be matched to conditions. If applicable, use process enclosures, local exhaust ventilation, or other engineering controls to maintain airborne levels below recommended exposure limits. If exposure limits have not been established, maintain airborne levels to an acceptable level.

Individual protection measures, such as personal protective equipment

Eye/face protection Wear safety glasses with side shields (or goggles).

Skin protection

Hand protection Wear appropriate chemical resistant gloves.

Skin protection

Other Wear appropriate chemical resistant clothing.

Respiratory protection If airborne concentrations are above the applicable exposure limits, use NIOSH approved

respiratory protection. Use a positive-pressure air-supplied respirator if there is any potential for an

uncontrolled release, exposure levels are not known, or any other circumstances where

air-purifying respirators may not provide adequate protection.

Thermal hazards Wear appropriate thermal protective clothing, when necessary.

General hygiene considerations

Observe any medical surveillance requirements. Always observe good personal hygiene measures, such as washing after handling the material and before eating, drinking, and/or smoking. Routinely wash work clothing and protective equipment to remove contaminants.

Contaminated work clothing should not be allowed out of the workplace.

9. Physical and chemical properties

Appearance

Physical state Liquid.
Form Liquid.
Color White.
Odor Slight.
Odor threshold Not available.

о**н** 7 - 10

Melting point/freezing point Not available.

Initial boiling point and boiling > 99 °F (> 37.2 °C)

range

SDS US

Flash point Not applicable.

Evaporation rate Not available.

Flammability (solid, gas) Not applicable.

Upper/lower flammability or explosive limits

Flammability limit - lower

(%

Not available.

Flammability limit - upper

(%)

Not available.

Vapor pressureNot available.Vapor densityNot available.

Relative density 1.16

Solubility(ies)

Solubility (water) Soluble

Partition coefficient Not available.

(n-octanol/water)

Auto-ignition temperature Not available.

Decomposition temperature Not available.

Viscosity 50 - 140 KU at 25°C

Other information

Density9.63 lbs/galExplosive propertiesNot explosive.Oxidizing propertiesNot oxidizing.

VOC 17 g/l (including water) (Material) 47 g/l (excluding water) (Coating)

10. Stability and reactivity

ReactivityThe product is stable and non-reactive under normal conditions of use, storage and transport.

Chemical stability Material is stable under normal conditions.

Possibility of hazardous

reactions

No dangerous reaction known under conditions of normal use.

Conditions to avoidContact with incompatible materials.

Incompatible materials Strong oxidizing agents.

Hazardous decomposition

products

No hazardous decomposition products are known.

11. Toxicological information

Information on likely routes of exposure

Inhalation Prolonged inhalation may be harmful.

Skin contact Causes mild skin irritation. May cause an allergic skin reaction.

Eye contact Direct contact with eyes may cause temporary irritation.

Ingestion Expected to be a low ingestion hazard.

Symptoms related to the physical, chemical and toxicological characteristics

May cause an allergic skin reaction. Dermatitis. Rash.

Issue date: 16-January-2020

Information on toxicological effects

Acute toxicity

Components Species Test Results

Titanium dioxide (CAS 13463-67-7)

Acute Oral

LD50 Rat > 5000 mg/kg

Skin corrosion/irritation Prolonged skin contact may cause temporary irritation.

 ${\tt BEHR} \hbox{\tt REMIUM PLUS Exterior Semi-Gloss Enamel - Medium Base}$

951421 Version #: 02 Revision date: 04-September-2020

Serious eye damage/eye

irritation

Direct contact with eyes may cause temporary irritation.

Respiratory or skin sensitization

Respiratory sensitization Not a respiratory sensitizer.

Skin sensitization May cause an allergic skin reaction.

Germ cell mutagenicityNo data available to indicate product or any components present at greater than 0.1% are

mutagenic or genotoxic.

Carcinogenicity Suspected of causing cancer.

IARC Monographs. Overall Evaluation of Carcinogenicity

Titanium dioxide (CAS 13463-67-7) 2B Possibly carcinogenic to humans.

NTP Report on Carcinogens

Not listed.

OSHA Specifically Regulated Substances (29 CFR 1910.1001-1053)

Not listed.

Reproductive toxicityThis product is not expected to cause reproductive or developmental effects.

Specific target organ toxicity -

single exposure

Not classified.

Specific target organ toxicity -

repeated exposure

Not classified.

Aspiration hazard Not an aspiration hazard.

Chronic effects Prolonged inhalation may be harmful.

12. Ecological information

Ecotoxicity Harmful to aquatic life with long lasting effects.

Persistence and degradability No data is available on the degradability of any ingredients in the mixture.

Bioaccumulative potential No data available.

Mobility in soil This product is water soluble and may disperse in soil.

Other adverse effects The product contains volatile organic compounds which have a photochemical ozone creation

potential.

13. Disposal considerations

Disposal instructionsCollect and reclaim or dispose in sealed containers at licensed waste disposal site. Incinerate the

material under controlled conditions in an approved incinerator. Dispose of contents/container in

accordance with local/regional/national/international regulations.

Local disposal regulations Dispose in accordance with all applicable regulations.

Hazardous waste code

The waste code should be assigned in discussion between the user, the producer and the waste

disposal company.

Waste from residues / unused

products

Dispose of in accordance with local regulations. Empty containers or liners may retain some product residues. This material and its container must be disposed of in a safe manner (see:

Disposal instructions).

Contaminated packaging Since emptied containers may retain product residue, follow label warnings even after container is

emptied. Empty containers should be taken to an approved waste handling site for recycling or

disposal.

14. Transport information

DOT

Not regulated as dangerous goods.

IATA

Not regulated as dangerous goods.

IMDG

Not regulated as dangerous goods.

Transport in bulk according to Not applicable.

Annex II of MARPOL 73/78 and

the IBC Code

BEHR® PREMIUM PLUS Exterior Semi-Gloss Enamel - Medium Base
951421 Version #: 02 Revision date: 04-September-2020 Issue date: 16-January-2020

15. Regulatory information

This product is a "Hazardous Chemical" as defined by the OSHA Hazard Communication **US** federal regulations

Standard, 29 CFR 1910.1200.

TSCA Section 12(b) Export Notification (40 CFR 707, Subpt. D)

2-Methyl-2H-isothiazol-3-one (CAS 2682-20-4) 1.0 % One-Time Export Notification only.

CERCLA Hazardous Substance List (40 CFR 302.4)

Diuron (CAS 330-54-1) Listed.

SARA 304 Emergency release notification

Not regulated.

OSHA Specifically Regulated Substances (29 CFR 1910.1001-1053)

Not listed.

Toxic Substances Control Act (TSCA) All components are listed on or exempt from the U.S. EPA TSCA Inventory

Superfund Amendments and Reauthorization Act of 1986 (SARA)

SARA 302 Extremely hazardous substance

Not listed.

SARA 311/312 Hazardous Yes

chemical

Classified hazard Respiratory or skin sensitization

Carcinogenicity categories

SARA 313 (TRI reporting)

Not regulated.

Other federal regulations

Clean Air Act (CAA) Section 112 Hazardous Air Pollutants (HAPs) List

Not regulated.

Clean Air Act (CAA) Section 112(r) Accidental Release Prevention (40 CFR 68.130)

Not regulated.

Safe Drinking Water Act

Not regulated.

(SDWA)

US state regulations

US. Massachusetts RTK - Substance List

Diuron (CAS 330-54-1)

Titanium dioxide (CAS 13463-67-7)

US. New Jersey Worker and Community Right-to-Know Act

Diuron (CAS 330-54-1)

Titanium dioxide (CAS 13463-67-7)

US. Pennsylvania Worker and Community Right-to-Know Law

Diuron (CAS 330-54-1)

Titanium dioxide (CAS 13463-67-7)

US. Rhode Island RTK

Diuron (CAS 330-54-1)

Titanium dioxide (CAS 13463-67-7)

16. Other information, including date of preparation or last revision

16-January-2020 Issue date 04-September-2020 **Revision date**

Version # 02

HMIS® ratings Health: 2*

Flammability: 0 Physical hazard: 0

SDS US BEHR® PREMIUM PLUS Exterior Semi-Gloss Enamel - Medium Base 6/7 951421 Version #: 02 Revision date: 04-September-2020 Issue date: 16-January-2020

List of abbreviations DOT: Department of Transportation (49 CFR 172.101).

IATA: International Air Transport Association.

IBC Code: International Code for the Construction and Equipment of Ships Carrying Dangerous

Chemicals in Bulk.

References

IMDG Code: International Maritime Dangerous Goods Code.

LC50: Lethal Concentration, 50%.

LD50: Lethal Dose, 50%.

MARPOL: International Convention for the Prevention of Pollution from Ships.

PEL: Permissible Exposure Limit. STEL: Short-Term Exposure Limit. TWA: Time Weighted Average Value.

HSDB® - Hazardous Substances Data Bank

IARC Monographs. Overall Evaluation of Carcinogenicity

Behr Process Corp cannot anticipate all conditions under which this information and its product, or Disclaimer

the products of other manufacturers in combination with its product, may be used. It is the user's responsibility to ensure safe conditions for handling, storage and disposal of the product, and to assume liability for loss, injury, damage or expense due to improper use. The information in the

sheet was written based on the best knowledge and experience currently available.

BEHR® PREMIUM PLUS Exterior Semi-Gloss Enamel - Medium Base

SDS US 951421 Version #: 02 Revision date: 04-September-2020 Issue date: 16-January-2020